



Product: <u>5002UP</u> ☑

Commercial Audio, 4 Conductor 12 AWG BC, CL3

Product Description

Commercial Audio Cable, 4 Conductor 12 AWG, highly flexible stranded (65x30) bare copper conductors with PVC insulation, CL3, PVC jacket with ripcord.

Technical Specifications

Product Overview Environmental Space: Indoor (Not Riser or Plenum) Physical Characteristics (Overall) Conductor AWG Stranding Material No. of Conductors 12 65x30 BC - Bare Copper 4 Conductor Count: 4

Insulation

Material	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.02 in

Color Chart



Outer Shield Material



Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness	Ripcord
PVC - Polyvinyl Chloride	0.365 in	0.022 in	Yes

Construction and Dimensions

Cabling

Twists

2.4 twist/ft

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR 1.56 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor 32 pF/ft

Inductance

Nominal Inductance

Current

Max. Recommended Current [A] 21 Amps per conductor @ 25°C A

Voltage

UL Voltage Rating 300 V RMS

Temperature Range

UL Temp Rating:	75°C
Operating Temp Range:	-20°C To +75°C

Mechanical Characteristics

Bulk Cable Weight:	117 lbs/1000ft
Max Recommended Pulling Tension:	338 lbs
Min Bend Radius/Minor Axis:	3.625 in

Standards

NEC/(UL) Specification:	CL3

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1685 UL Loading
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

No	
	No

Part Number

Variants

Item #	Color	UPC	Length
5002UP 0101000	Black	612825155799	1,000 ft
5002UP 010500	Black	612825155720	500 ft
5002UP D15500	Blue	611589226523	500 ft
5002UP 0081000	Gray	612825155751	1,000 ft
5002UP 008500	Gray	612825155768	500 ft
5002UP 005500	Green, Dark	612825155744	500 ft
5002UP 0091000	White	612825155775	1,000 ft
5002UP 009500	White	612825155782	500 ft

History

Update and Revision: Revision Number: 0.282 Revision Date: 01-31-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.