RC400T event controller Ref. RC400T



Event controller for the LivePremier™ multi-screen live presentation systems



Presentation

The RC400T event controller has been designed to greatly increase the level of operational efficiency and to give instant access to the crucial functionalities of the LivePremier™ image processor such as screens, layers, sources and memories. The RC400T comes with a small footprint design and rugged housing, and offers 56 user programmable buttons, a high-resolution T-bar and a three-axis joystick for easy and fast PIP sizing and programming. This makes it the perfect solution for most control environments from large-scale live events (music shows, product launches, industry conferences...) to multi-purpose event auditoriums.



Technical Specifications

W 22.44" x H 4.82" x D 15.04" ► 100-240 VAC 50/60Hz 2.2A L 570 mm x H 122.5 mm x P 382 mm ► Fuse cartridge T2,5A 250VAC 5x20mm ► Max consumption: 25 W Weight without accessories ▶ 8 kg / 17.63 lbs Safety Compliance ► IEC/UL/EN 62368-1 **Operating conditions** Temperature: 0 to 40°C (32 to 104°F) ▶ (UL Listed E359143) ► Humidity: 10% to 80%, non-condensing **EMC & Environnemental Compliance** Noise (@1,6m height @25°C) ► EN55032, EB55024, EN61000, FCC Front: 35 DBa@1m part15, ICES ► Rear: 35 DBa@1m Supplied with Thermal dissipation ▶ 1 x Power supply cord ▶ 85 BTU/hr ▶ 1 x Quick start guide including safety Warranty 3-year warranty on parts and labor back to

Specifications subject to change without prior notice

Key Features

Heavy-duty, compact design

Designed for fault-free operation

Instant access to crucial functionalities

56 user-programmable buttons

High-resolution T-bar

Three-axis joystick for easy and fast PIP sizing and programming

1 USB (front panel) and 1 USB (rear panel)

1 Ethernet network interface

Can be deployed both on a desk or recessed in the console surface

1 4-pin XLR connector XLR for LED lamp (sold as an option)

RC400T_EN-02/07/2020







